CIN NO.: U74899DL1968GO1004866 आईएसओ 9001:2008 न्यू भोपाल टेक्सटाइल मिल्स, भोपाल GST No.: 23AAACN2847D1ZW प्रमाणित संस्थान चांदबद, भोपाल-462010 (म.प.) (नेशनल टेक्सटाइल कारपोरेशन लि. नई दिल्ली की इकाई) Chandbarh, Bhopal-462010 (MP) (भारत सरकार का उपकम) GM Office : (0755)2742412 Fax: (0755)2746728 NEW BHOPAL TEXTILE MILLS, BHOPAL NTC : www.ntcltd.org (Unit of National Textile Corporation Ltd., New Delhi) NTC E:mail ntcmpnbt@vahoo.com (A Government of India Undertaking) ISO 9001:2008 **CERTIFIED COMPANY**

क. स्टोर्स/22

.....

.....

Enquiry No. 5

DATE: 10.06.2022 Due date: - 18.06.2022 by 4PM Tender opening date :- 18.06.2022 at 5PM

प्रति,

<u>Sub:</u> Enquiry for supply and installation of Electromagnetic / ultra sonic water flow meter with telemetry and supply and installation of Piezometer as per Central Ground Water Authority Guidelines and specifications.

प्रिय महोदय Dear Sir,

निम्नलिखित माल के बावत् हम आपके कम से कम भाव के निविदा का सहर्ष स्वागत करते हैं। जहाँ पर आवश्यकता हो आप माल के सेम्पल भी संलग्न करें। कृपया आप भाव–पत्र मोहर बंद लिफाफे मे पैक करके उसके ऊपर कोटेशन इन्क्वायरी नंबर और अंतिम तिथि लिखकर भेजें।

We welcome to your lowest quotations for the following items. Please send samples of the item whenever necessary. Please send your quotation in seal packed envelop duly mentioned the Quotation Enquiry Number & due date on top of envelope.

विशेष सूचना :- जो पूर्तिकर्ता ने लघु उद्योग अनुसूचित जाति / जनजाति के अंतर्गत पंजीकरण किया है। ऐसे पूर्ति को विशेष प्राधान्य दिया जाएगा, मगर उन्हें अपने पंजीकरण के प्रमाण-पत्र की छायाप्रति इन्क्वायरी के साथ लगाना अनिवार्य है।

Note:- The parties who are registered with MSME including SC/ST category will be given preference. The bidder should submit the supporting documents regarding their registration with MSME along with the Enquiry.

9 .

NEW BHOPAL TEXTILE MILLS, BHOPAL

INVITATION FOR BIDS

1. Eligibility criteria:-

Tenders are invited for "supply and installation of Electromagnetic / ultra sonic water flow meter with telemetry and supply of Piezometer as per Central Ground Water Authority Guidelines and specifications.

The Bidder should be original equipment manufacturer (OEM) or authorized sales & service representative of OEM in INDIA The bidder should furnish the following documents in support

- 1. OEM: The bidder has offered his own make/model of the system
- 2. Authorized sales & service representative: The bidder should furnish valid authorization from OEM for sales and service of the offered system in India.
- 3. The bidder should have valid PAN and also GST (copies to be enclosed).
- 2. Scope of work

S.No.	Item Description	QTY.	Price in Rs.
1.	SUPPLY OF ELECTROMAGNETIC FLOWMETER WITH TELEMETRY, 3" PIPE DIAMETER	1	
2.	SUPPLY OF PIEZO METER	1	-
3.	NABL ACCREDITED CERTIFICATE for one year of ELECTROMAGNETIC FLOWMETER	1	
4.	INSTALLATION & COMMSSIONNING Charges FOR BOTH THE METERS	1	

The terms and conditions are as under:

1. SGST%:-....

2. CGST%:-....

3. IGGT%:-....

4. UGST%:-....

5. Payment :- 30 days after completion of work

6. Delivery and installation: - before 30th june 2022.

7. Tax Invoice Necessary

8. Freight:- inclusive in the above rates

9. Party Must Rubber Seal/Stamp/Sign before submitting the tender.

10. Party must fill the Tender in our format only.

Location of Plant:

Address:New Bhopal Textile Mills,Bhopal Near Railway station Chandbarh,Bhopal Pin code:462010 Contact Person :- Yogender Prasad Mobile No. 7470960207 Daily consumption-95 KLD No of bore wells- 04 Nos. (10 H.P each) Plant land area-84.1 acers

Technical specifications

1. Specification of Tamper proof Electronic water meter with telemetry (Digital Water Flow Meter with Telemetry for Groundwater extraction monitoring as per CGWA notification)

Metering Technology Communication type

Tamper proof:

a) Power source

b) Sealing

Compliance

Accuracy

Test certificate

: Ultrasonic or Electromagnetic : LAN (for internet connectivity) or LoRa WAN and/or Cellular (GPRS / 3G / 4G)

: The meter shall be battery operated or UPS powered supply with provision of power OFF Detection.

The telemetry system units shall be battery operated or through external power supply. The metering data should be stored in the meter even if the telemetry system is off due to power failure.

: The meter and telemetry system shall have proper mechanical and electronic sealing (through software) arrangement. Any attempt to open the meter or system enclosure should physically damage the tag.

: The meter shall preferably be manufactured as per ISO 4064: 2014 Standards and shall have IP 68 ingress protection.

: The meter shall be of accuracy better than $\pm 2\%$ for the operating flow range (from 10 % to 100 % of maximum flow rate).

: The meter manufacturer shall submit the latest test/calibration certificate of the meter, from Fluid Control Research Institute (FCRI) / National Physical Laboratory (NPL) or any third party laboratory accredited by National Accreditation Board for Testing and Calibration Laboratories (NABL), for every meter.

Parameters to monitor

: The meter (since installation of the requisite water meter) shall transmit the following parameters to a secure cloud • Timestamp

- Cumulative forward flow volume
- Cumulative reverse flow volume
- Cumulative Net volume
- Cumulative pump working hours
- Meter serial number
- Device last calibration date
- Borewell id (Provided by CGWA)

: The Communication / telemetry data should be directly captured in a secure cloud. The cloud service provider should be empanelled with The Ministry of Electronics and Information Technology (MeitY).

: The data shall be transmitted minimum 2 times in a day

: In case of battery operated meters the battery shall run at least for a period of 3 years with 2 transmissions per day. The battery shall be replaceable without any data loss.

: The meter shall be supplied with complete AMR / AMI system with Data Management software. The Data Management Software must be capable of running on a standard PC. The Data Management Software should be cloud based and should have web portal access so that user can view customer data through browser. In addition to above, Data Management Software will be installed on Server placed in Central Data Base/Control Room, and the software may have option for individual customer to view their meter consumption data through Web portal. Consumer, engineer and manager screens shall be available separately.

Data Collection Unit shall be capable of taking data from meter, pump etc. and should be posted in Data Management Software.

Cloud

Transmission frequency

Battery life

Data acquisition

Real-time data to CGWA

2. Installation of meter

Location

Bypassing

Full flow

: The un-tampered data from the secure cloud shall be sent to Central Ground Water Authority (CGWA) real-time data management platform once it is ready. Proper cyber security measures shall be taken in the secure cloud.

: The meter shall be installed at the borewell pump discharge line before any branching and preferably as shown in Figure. 1

: There shall be no bypassing of pipe prior to the installed flow meter. : The installation of the meter shall ensure the pipe shall have full of water at all times. Sufficient upstream and downstream straight length shall be provided for the meter (Refer to Figure 1.)



Figure. 1 Installation position of tamper proof flow meter with telemetry at groundwater abstraction structures

۹.

3. DETAILED TECHNICAL SPECIFICATIONS OF AMR / AMI WATER FLOW METERS

Flow meters shall meet the following metrological specification: Turndown ratio of 10 or above Accuracy ± 2%

Technology: electromagnetic or ultrasonic

3.1.1 Size:

- 1. DN40 Flow range: 0.5 lps to 5 lps
- 2. DN100 Flow range: 3 to 30 lps
- 3. DN150 Flow range: 13 to 130 lps

Meter performance shall not get affected by external magnetic field, as specified in ISO4064. Meters must be able to retain their accuracy, when installed in either horizontal and/or vertical

3.1.2 Material of Construction:

The manufacturer shall provide specific details of materials used for various parts of the meter which must meet the specifications for the material of construction of the individual parts of the meters as per applicable standards (referred above).

- The water meter and accessories shall be manufactured from materials of adequate
- The body of the meter shall be of Brass/Bronze/MS/CI/SS/Engineering Plastic and compact enough to avoid tampering of meter. The manufacturer shall specifically mention in the offer, the material used in manufacturing.
- The materials, which come in contact with the potable water, shall not create a toxic • hazard, shall not support microbial growth, and shall not give rise to unpleasant taste, odor or discoloration in the water supply.
- The painting material used should be free from toxic constituents and safe for human uses •
- and should not affect human health (Health Certificate should be attached/provided). Each meter should be supplied in separate individual box with its accessories, test/ calibration Certificate (for accuracy parameter) and Guarantee Card for free repair/replacement during the warranty period.

3.1.3 Markings on the Body of the Meter:

- Make/Brand, Size / Nominal Dia.
- o SI. No. / Year of Manufacture, Metrological specifications etc.

3.1.4 Meter indicator

The digital indicator shall be designed in such a way that if the protective glass is broken for a reason or another, the indicator cannot be removed from its place. The protective cover of the indicator shall be made of sturdy glass/PP/PC.

o It shall be of straight reading type.

 $\circ\,$ No. of digits and verification scale interval shall be as sufficient enough to meet the required

Totalizer shall be made of suitable material required to maintain IP 68 protection class.

۹.

3.2 Telemetry System

- The AMR/AMI system should have the facility to detect and communicate any abnormalities, i.e. high consumption, tampering etc. along with necessary alarms.
- The system will communicate in real time for battery and tamper alarms, in order to provide relevant monitoring and management data for operational purposes.
- The battery shall be replaceable without any data loss.
- The meters should report an alarm to the server as and when tampered. All Water Meter readings should be time stamped.
- The meter should have the capability to detect and record reverse flow separately.
- The meter should be capable of to detect Leak, Zero (No) Flow, High Flow. The AMR/AMI should operate even in electrically noisy environments with electromagnetic interference. The AMR/AMI should function even in the presence of high
- Battery usage has to be indicated at the server. Provision should be provided to replace
- The communication shall be encrypted to avoid tampering. •
- The meter should be configurable either using the DTU or from the server. Loss of communication should be indicated in the server within 48 hours. •
- The meter should be able to log the daily flow data with a timestamp which is supposed to . be sent to the cloud via telemetry for at least 2 years.
- In case the telemetry is non-functional because of power cut or weak cellular signals, the • meter should be able to store the data and transmit to the cloud as soon as the telemetry
- This data shall also be used for retrieval in case of any dispute between meter data and

3.3 Data Management Software

- The web based Data Management Software must be capable of running on a standard PC compatible with minimum Pentium Processor; in addition, the software must run under Windows XP Professional, Windows Vista, Windows 7 and / or latest version of Windows Operating System and HP Unix, Linux,
- The Data Management Software should be cloud base and should have web portal access so that user can view customer data through browser. In addition to above, Data Management Software will be installed on Server placed in Central Data Base / Control Room, and the software may have option for individual customer to view their meter consumption data through Web portal.
- The Data Management Software shall provide database backup/restore functions and . must have real-time data access. The software should be web-enabled and alerts to be provided through email/SMS to the user.
- The Data Management Software shall post the reading from the communication . infrastructure on to appropriate accounts within the Database.
- The Data Management Software should be able to display all kind of data on screen at
- The Data Management Software should have capability to add additional customer information and create customizable data fields.

3.4 Lab Testing / calibration:

Testing or Calibration of meters shall be performed at ISO 17025: 2017 accredited laboratory. The accuracy of meter shall be within ± 2 % in the operating range. The meter shall have valid model approval certificate.

The meter shall have model approval from India or abroad. Every meter should be calibrated / tested for accuracy in the operating flow range (10% to 100%). At least 4 point calibration at 10%, 40%, 70% and 100% of maximum/rated flow shall be performed.

2. Specification of Piezometer (Digital Water Level Recorder/indicator)

- Cable Length: 150 meters
- Output: RS 485
- 100 FT WATER PROOF CABLE
- 100 FT RANGE PIEZOMETER SENSOR
- ALL ACCESSORIES
- (WALL MOUNT CLAMP WITH NUT AND BOLT,
- INDICATOR PLAT)
- SS 316 SENSOR
- SS 316 HOUSING
- IP68 ENCLOSURE(SINTEX BOX)

3. **REJECTION OF THE TENDER.**

- a. New Bhopal Textile Mills, Bhopal (MP) reserve the right to accept or reject all or any of the tender without assigning any reason what so ever. It is not obligatory for the mills to give any reason for their decisions.
- b. New Bhopal Textile Mills, Bhopal (MP) reserve the right not to proceed with the tendering process at any time without notice or liability and to reject any tender without assigning any reasons. New Bhopal Textile Mills, Bhopal (MP) also reserve the right to re-tender without assigning any reason what so ever.

4. **RESOLUTION OF DISPUTES.**

The Terms & Condition of this tender document shall prevail in case of any dispute arising out of this contact and any dispute directly or indirectly connected with this contract will be referred to sole arbitration of the Chairman & Managing Director of National Textile Corporation Ltd. New Delhi or any other officer appointed by the Chairman-cum- Managing Director of the corporation for this purpose. The decision of the said arbitrator shall be final, conclusive and binding upon all concerned.

5. <u>JURISDICTION</u>

All suits or proceedings relating to any dispute or claim arising out of or in course of performance in this contract shall be filed in appropriate court having jurisdiction in the state of Madhya Pradesh only.

6. OTHER TERMS & CONDITIONS.

- 1. The bidders may visit the mill between 10 am to 4.00 pm for more clarification and information about the bid.
- 2. Delivery and installation: before 30^{th} june 2022.
- 3. TDS / Income Tax and other taxes if any, will be deducted as per prevailing Government rules.

Prepared By :

Jt. Mgr. (Store)

Yours faithfully General Manager (I/c)

4. **RESOLUTION OF DISPUTES.**

The Terms & Condition of this tender document shall prevail in case of any dispute arising out of this contact and any dispute directly or indirectly connected with this contract will be referred to sole arbitration of the Chairman & Managing Director of National Textile Corporation Ltd. New Delhi or any other officer appointed by the Chairman-cum-Managing Director of the corporation for this purpose. The decision of the said arbitrator shall be final, conclusive and binding upon all concerned.

5. JURISDICTION

All suits or proceedings relating to any dispute or claim arising out of or in course of performance in this contract shall be filed in appropriate court having jurisdiction in the state of Madhya Pradesh only.

6. OTHER TERMS & CONDITIONS.

- 1. The bidders may visit the mill between 10 am to 4.00 pm for more clarification and information about the bid.
- 2. Delivery and installation: before 30^{th} june 2022.
- 3. TDS / Income Tax and other taxes if any, will be deducted as per prevailing Government rules.

Prepared By :

Jt. Mgr. (Store)

Yours faithfully General Manager (I/c)

6. <u>ACCEPTANCE OF THE TENDERER</u>.

۹.,

We have read all the terms and conditions attached with tender document and we agree to abide by the same.

Name of the firm _	
Address	
Contact No.	-
Email	

Signature & Seal

11 | Page